

BragGrate[™]- Bandpass Filter Reflecting Bragg Grating (RBG) for spectral filtering

Product Description **///**

BragGrate[™] Bandpass Filter is a reflecting Bragg grating (RBG) recorded in a bulk of photosensitive silicate glass. The filters are used to clean up laser spectral noise with a bandwidth as narrow as 100 pm in visible and near IR regions. In Raman spectroscopy applications, combining the Bandpass Filters with matching BragGrate[™] Notch Filters enables Raman shift measurements down to 5 cm⁻¹ from the laser line. BragGrate[™] filters have superior environmental stability and can handle high power optical radiation.

Standard Parameters ///

Center Wavelength: 405, 488, 514, 532, 633, 785, 1064 nm

Spectral Bandwidth (FWHM): < 7 cm⁻¹

Diffraction Efficiency: > 90%

Lateral Dimensions: 5×5 mm²

Total Deflection Angle: 20 deg

Applications

Spectral filtering and noise cleaning of laser beams

- ASE filters for Raman laser sources
- Spectral detection
- Tunable filters for high resolution spectroscopy

Specifications ///


Diffraction Efficiency (DE): >90%
Spectral Bandwidth: 0.1 to 0.5 nm
Operating Range λ: 400-2500 nm
Grating Thickness: 1.5-10 mm
Apertures: up to 10×10 mm ²
Deflection Angles: 5-90 deg

Advantages & Features ///


• High spectral selectivity

1

- Superior environmental stability, no degradation over lifetime
- High power operations over 1 kW
- High average power operations >20 W
- High energy operations up to 5 J/cm²
- No polarization dependence
- Near-diffraction-limited beam quality



785 nm laser diode ASE background clean up with a BragGrate[™] bandpass filter with bandwidth <7 cm⁻¹



Schematics of a possible BragGrate[™] Bandpass filter configuration



OptiGrate Corp designs and manufactures a full range of BragGrate[™] holographic optical elements (volume Bragg gratings) in inorganic photosensitive silicate glass. OptiGrate pioneered commercial VBG technology and supplied VBG-based diffractive optical components to hundreds of customers on 5 continents. This technology is protected by a portfolio of issued and pending patents.

1