






BragGrate[™] - Pulse Stretcher & compressor for ultra-short pulse lasers

Product Description




BragGrate[™]-Pulse is a volume Bragg grating in reflecting geometry with a period gradually varying along the direction of the beam propagation (so-called chirped Bragg grating, CBG).

BragGrate[™]-Pulse is the first commercially available CBG-based product especially designed for stretching / compression of femtosecond and picosecond laser pulses.

Product Features ""

- Compact geometry and easy-to-align
- High power operation (up to 1 kW average power)
- High energy operation (up to 2 mJ pulse energy)
- Environmentally stable
- Robust, easy to handle and clean
- Preserves diffraction limited quality of femtosecond laser beam with diffraction efficiency exceeding 80%



Output beam shape after passing 30-mm-thick CBG in both directions

Specifications ///

Spectral bandwidth: 1-100 nm
Operating range: 800-2500 nm

Thickness: 10-50 mm

Stretching time: 10-250 ps (FWHM)

Efficiency: 70-95%

Apertures: up to 8x10 mm²

Applications ""

BragGrate™-Pulse is for temporal stretching of a reflected ultrashort pulse and recompression of this pulse if launched from the opposite side of the grating. Most compact and robust compressors are ideal for industrial and scientific applications.

Typical Specs of BragGrate™- Pulse for 1030 nm spectral range ///

Center wavelength: 1032 nm

Spectral bandwidth: 5, 10, 25 nm


Diffraction efficiency: > 85%

Thickness: 20, 35 mm

Stretching time (FWHM): ~ 150 ps

Dispersion rate: ~ 6, 10, 25, 60 ps/nm (linear)

Compressed pulse duration: < 200 fs



Compressed pulse profile theoretical vs measured data with 30 mm thick BragGrate™ Pulse





